



**CS&CV
Cables**

95ASE1230

CS-A1-06-U-05

**CONNECTION CABLE 8
POLES WITH M12 AXIAL
CONNECTOR**

OVERVIEW

- M8 and M12, axial or radial female connectors
- Standard length cables: 2, 3, 5, 7, 10, 15, 25 or 50m
- 3, 4, 5, 8 or 12 poles
- Shielded or unshielded models
- P.U.R. coated models for use in harsh environments
- P.V.C. coated models for standard use
- Standard M12 4 pole non-cabled connectors
- The cable jacket maybe marked 300V only as insulation voltage between wires, the operational voltage is 24Vdc or 10-30Vdc, less than 80 V required by CCC-China

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	n/a
controlled height	n/a
Sensitivity adjustment	n/a

Application

Description	Straight female
-------------	-----------------

Functions	Cable/connector
-----------	-----------------

Safety parameters

Type	Safety accessory
------	------------------

Outputs

Output type	n/a
-------------	-----

Response time	n/a
---------------	-----

Electrical data

Operating Voltage	10-30 VDC
-------------------	-----------

Emission	n/a
----------	-----

Mechanical data

Dimensions	L=5m
------------	------

Connections	M12 8-poles
-------------	-------------

Material	PVC UL style 2464
----------	-------------------

Generical Data

Dimensions	L=5m
------------	------

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

28/06/2024
07:47:28